

〈鋼管規範重量表〉

勝公貿易股份有限公司
宏承鋼鐵股份有限公司

公司(貿易部): 台北市興安街78~11號

TEL: (02)25022286 • 25028175 • 25038881

FAX: (02)25034704

倉庫(業務部): 桃園縣龜山鄉頂湖六街6號

TEL: (03)397-3688 (總機)

(03)328-8132 • (03)328-8028~9

FAX: (03)397-3666 • (03)328-8133

JIS (日本工業規格協會)

JIS G3452 SGP

JIS G3454 STPG

JIS G3455 STS

JIS G3456 STPT

JIS G3460 STPL

名稱		外徑 (mm)	外徑厚度 (mm)											外徑 (mm)
(A)	(B)		S. G. P.	Sch. 10	Sch. 20	Sch. 30	Sch. 40	Sch. 60	Sch. 80	Sch. 100	Sch. 120	Sch. 140	Sch. 160	
6	1/8	10.5	2.0 0.419				1.7 0.369	2.2 0.450	2.4 0.479					10.5
8	1/4	13.8	2.3 0.652				2.2 0.629	2.4 0.675	3.0 0.799					13.8
10	3/8	17.3	2.3 0.851				2.3 0.851	2.8 1.00	3.2 1.11					17.3
15	1/2	21.7	2.8 1.31				2.8 1.31	3.2 1.46	3.7 1.64				4.7 1.97	21.7
20	3/4	27.2	2.8 1.68				2.9 1.74	3.4 2.00	3.9 2.24				5.5 2.94	27.2
25	1	34.0	3.2 2.43				3.4 2.57	3.9 2.89	4.5 3.27				6.4 4.36	34.0
32	1 1/4	42.7	3.5 3.38				3.6 3.47	4.5 4.24	4.9 4.57				6.4 5.73	42.7
40	1 1/2	48.6	3.5 3.89				3.7 4.10	4.5 4.89	5.1 5.47				7.1 7.27	48.6
50	2	60.5	3.8 5.31		3.2 4.52		3.9 5.44	4.9 6.72	5.5 7.46				8.7 11.1	60.5
65	2 1/2	76.3	4.2 7.47		4.5 7.97		5.2 9.12	6.0 10.4	7.0 12.0				9.5 15.6	76.3
80	3	89.1	4.2 8.79		4.5 9.39		5.5 11.3	6.6 13.4	7.6 15.3				11.1 21.4	89.1
90	3 1/2	101.6	4.2 10.1		4.5 10.8		5.7 13.5	7.0 16.3	8.1 18.7				12.7 27.8	101.6
100	4	114.3	4.5 12.2		4.9 13.2		6.0 16.0	7.1 18.8	8.6 22.4		11.1 28.2		13.5 33.6	114.3
125	5	139.8	4.5 15.0		5.1 16.9		6.6 21.7	8.1 26.3	9.5 30.5		12.7 39.8		15.9 48.6	139.8
150	6	165.2	5.0 19.8		5.5 21.7		7.1 27.7	9.3 35.8	11.0 41.8		14.3 53.2		18.2 66.0	165.2
200	8	216.3	5.8 30.1		6.4 33.1	7.0 36.1	8.2 42.1	10.3 52.3	12.7 63.8	15.1 74.9	18.3 88.9	20.6 99.4	23.0 110	216.3
250	10	267.4	6.6 42.4		6.4 41.2	7.8 49.9	9.3 59.2	12.7 79.8	15.1 93.9	18.2 112	21.4 130	25.4 152	28.6 168	267.4
300	12	318.5	6.9 53.0		6.4 49.3	8.4 64.2	10.3 78.3	14.3 107	17.4 129	21.4 157	25.4 184	28.6 204	33.3 234	318.5
350	14	355.6	7.9 67.7	6.4 55.1	7.9 67.7	9.5 81.1	11.1 94.3	15.1 127	19.0 158	23.8 195	27.8 225	31.8 254	35.7 282	355.6
400	16	406.4	7.9 77.6	6.4 63.1	7.9 77.6	9.5 93.0	12.7 123	16.7 160	21.4 203	26.2 246	30.9 286	36.5 333	40.5 365	406.4
450	18	457.2	7.9 87.5	6.4 71.1	7.9 87.5	11.1 122	14.3 156	19.0 206	23.8 254	29.4 310	34.9 263	39.7 409	45.2 459	457.2
500	20	508.0	7.9 97.4	6.4 79.2	9.5 117	12.7 155	15.1 184	20.6 248	26.2 311	32.5 381	38.1 441	44.4 508	50.0 565	508.0
550	22	558.8		6.4 86.5	9.5 129	12.7 171	15.9 213	22.2 294	28.6 374	34.9 451	41.3 527	47.6 600	54.0 672	558.8
600	24	609.6		6.4 94.5	9.5 141	14.3 210	17.5 256	24.6 355	31.0 442	38.9 547	46.0 639	52.4 720	59.5 807	609.6
650	26	660.4					18.9 299	26.4 413	34.0 525	41.6 635	49.1 740	56.6 843	64.2 944	660.4
(A)	(B)	(mm)	S. G. P.	Sch. 10	Sch. 20	Sch. 30	Sch. 40	Sch. 60	Sch. 80	Sch. 100	Sch. 120	Sch. 140	Sch. 160	(mm)

END : 1 1/2" & under plain square cut ends
2" & above bevelled ends